

# PM135

## MULTIFUNCTIONAL POWERMETER



The PM135 is a multi-functional three-phase power meter with basic revenue metering, power quality and harmonics analysis.

The PM135 provides a cost-effective substitute for numerous analog meters used by industrial, commercial and utility customers for basic power metering.

The PM135 is widely integrated in panel boards and SCADA systems. With the addition of the unique TOU module, the EH model answers the needs of revenue metering applications. It is also suitable for utility substation automation with its support of the industry standard DNP 3.0, Modbus RTU and IEC 60870-5-101/104 protocols, as well as its I/O capabilities (using the Digital Input/Output modules).

The PM135 series consists of two basic models providing digital measurements of more than 80 electrical parameters locally, and more than 100 electrical parameters via RS-485 interface.

The PM135 has a 3x2" / 76x49mm backlit LCD display as well as SATEC's unique bar graph loading indicator.

### Measurement & Communication

The PM135 accurately measures over 100 parameters from basic frequency, voltages and currents, to all power parameters, four quadrant active, reactive and apparent energies, harmonics and time of use (TOU).

The PM135 has an integral RS-485 communication port for a wide range of protocols—Modbus, DNP 3.0 and IEC 60870. Its expansion module allows connection of a second communication port, including Ethernet, Profibus, RF or GPRS, as well as second RS-485 and RS-232 ports.

### Models

#### Measurement Features

- PM135P** Multi-functional 3-phase power meter functionality (see Features)
- PM135E** All the features of the P model plus Revenue Meter (see Features)
- PM135EH** All the features of the E model plus Power Quality control (see Features)

#### Current Inputs

- 1A** Standard 1A CT
- 5A** Standard 5A CT
- RS5** Remote Split Core for Standard 5A CT
- HACS** High Accuracy Current Sensors

## Features

### Multifunctional 3-Phase Power Meter

- Voltage, current (including neutral current), power, energy, power factor, frequency, voltage/current unbalance
- Current range up to 200%
- Supported frequencies: 25, 50, 60 and 400 Hz
- Direct connection up to 690V L-L (up to 1.15 MV via PT)

### Basic Power Quality Control (EH Model)

- Individual voltage and current harmonics (up to the 40<sup>th</sup>)
- Voltage and current THD, TDD & K-Factor
- Time stamped max/min values
- Waveforms 128 samples/cycle (via comm.)

### Revenue Meter (EH Model)

- Exceeds accuracy class 0.5S
- Time Of Use (TOU) tariffs

### Event/Data Log (EH Model)

- System events & data logging
- Real-time stamps

### Harmonic Analyzer (EH Model)

- Voltage and current THD, current TDD and K-Factor, up to 40th order harmonic
- Voltage and current harmonic spectrum and angles

### Real-time Waveform Capture

- Real-time “scope mode” waveform monitoring
- Simultaneous 6-channel one-cycle waveform capture at a rate of 64 samples per cycle

### Billing/TOU Energy Meter (E & EH Models)

- Class 0.5S IEC 62053-22 four-quadrant active and reactive energy polyphase static meter
- Three-phase total and per phase energy measurements; active, reactive and apparent energy counters
- Time-of-Use, 4 totalization and tariff energy/demand registers x 8 tariffs, 4 seasons x 4 types of days, 8 tariff changes per day,
- One-time easy programmable tariff calendar schedule
- Automatic daily energy and maximum demand profile log for total and tariff registers

### Communications

- Standard 2-wire RS-485 communication port
- Protocols: Modbus RTU, ASCII, DNP3.0, Optional IEC 60870-5-101; With Ethernet Modbus/TCP, DNP3/TCP; Optional IEC 60870-5-104 and with GPRS module: Modbus/TCP
- ExpertPower™ client for communicating with SATEC ExpertPower™ Internet services (with Ethernet or GPRS modules)
- TCP notification client for communicating with a remote Modbus/TCP server on events or periodically on a time basis (with the Ethernet or GPRS module)

### Alarm and Control Functions

- 16 programmable set points
- 4 counters

### Programmable Logical Controller

- Embedded programmable controller
- 16 control setpoints; programmable thresholds and delays
- Relay output control
- 1-cycle response time

## Event and Data Recording (E & EH)

- Non-volatile memory for long-term event and data recording
- Event recorder for logging internal diagnostic events and setup changes
- Two data recorders; programmable data logs on a periodic basis; automatic daily energy and maximum demand profile log

## I/O Options

- TOU+4DI module – four digital inputs with 1-ms scan time and battery backup for the real time clock; automatic recording of last five digital input change events with timestamps (see the PM135 Modbus Reference Guide)
- 4DIO – four digital inputs and two relay outputs with 1-cycle update time; unlatched, latched, pulse and KYZ operation; energy pulses, selection of solid state or electromechanical relays
- 12DIO – twelve digital inputs, 4 relay outputs and optional Ethernet or RS-485 communication port
- 4AO - four optically isolated analog outputs with an internal power supply; Selection of 0-20mA, 4-20mA, 0-1mA, and  $\pm 1$ mA output; 1-cycle update time

## Real Time Clock

- Built-in clock and calendar functions
- Internal clock with 20-second retention time
- Optional battery backup (TOU+4DI module)

## Power Supply

- Multi-purpose AC/DC power supply (85-265V AC, 88-290V DC)
- Special versions (12, 24-48V DC)

## Measurement

- Direct voltage measurement of up to 690v
- Selection of current input connections:
  - 5A – measurement of up to 10A using conventional 5A CTs

- 1A – measurement of up to 2A using conventional 1A CTs
- RS5 – allowing connection remotely of 5A conventional CTs with split core remote sensors
- HACS - selection of remote sensors up to 1200A with built in shorting circuit and class 0.5s system accuracy (meter plus CTs)

## Unique Design

- Pass-through CT connection provides minimal burden
- Auxiliary CT connection terminal for simple installation
- Add on modular design to add second communication port, digital I/O or Analog outputs



## Meter Security

- Password security for protecting meter setups and accumulated data from unauthorized changes

## Upgradeable Firmware

- Easy upgrading device firmware through a serial or Ethernet port

## Software Support

- PASTM – SATEC’s bundled software for meter configuration and data acquisition, including waveforms, phasors, harmonics and more
- ExpertPower™ – SATEC’s unique Internet services offer the industry leading energy management software (EMS) without client software installation

## Construction

- Dual panel mounting:
  - 4" Round; Square 96x96 DIN
- Weight: 1.5 lbs / 0.7 kg
- HxWxD: 4.5x4.5x4.3" / 114x114x109 mm
- One add-on module

## Technical Specifications

ENVIRONMENTAL CONDITIONS	
Operating temperature	-30°C to 60°C (-22°F to 140°F)
Storage temperature	-40°C to 85°C (-40°F to 185°F)
Humidity	0 to 95% RH non-condensing
CONSTRUCTION	
Weight	0.70kg (1.54 lb.)
Dimensions [H×W×D]	114×114×109mm (4.5×4.5×4.3")
MATERIALS	
Case enclosure	plastic PC/ABS blend
Front panel	plastic PC
PCB	FR4 (UL94-V0)
Terminals	PBT (UL94-V0)
Connectors-Plug-in type	Polyamide PA6.6 (UL94-V0)
Packaging case	Carton and Stratocell® (Polyethylene Foam) brackets
Labels	Polyester film (UL94-V0)
POWER SUPPLY	
120/230V AC-DC Option	→ Rated input: 85-265V AC 50/60/400 Hz, 88-290VDC, Burden 9VA → Isolation: 2500V AC (Input to ground)
12 VDC Option	→ Rated input: 9.5-18V DC, Burden 4VA → Isolation: 1500V DC
24/48 VDC Option	→ Rated input: 18.5-58 VDC, Burden 4VA → Isolation: 1500VDC → Wire size: up to 12 AWG (up to 3.5 mm <sup>2</sup> )

INPUT RATINGS	
VOLTAGE INPUTS	
Operating range	690VAC line-to-line, 400VAC line-to-neutral
Direct input and input via PT	up to 790VAC line-to-line, up to 460VAC line-to-neutral
Input impedance	1000 kΩ
Burden for 400V	< 0.4 VA
Burden for 120V	< 0.04 VA
Over-voltage withstands	1000 VAC continuous, 2000 VAC for 1 second
Wire size	up to 12 AWG (up to 3.5mm <sup>2</sup> )
CURRENT INPUTS (Via CT)	
Wire size	12 AWG (up to 3.5 mm <sup>2</sup> )
Galvanic isolation	3500 VAC
5A SECONDARY or 5A REMOTE SENSOR (RS5)	
Operating range	Continuous 10A RMS
Burden	< 0.2 VA @ I <sub>n</sub> =5A (with 12AWG wire and 1 m long)
Overload withstand	15A RMS continuous, 300A RMS for 1 second (with 12AWG section wire)
1A SECONDARY	
Operating range	Continuous 2A RMS
Burden	< 0.02 VA @ I <sub>n</sub> =1A (with 12AWG wire and 1 m long)
Overload withstand	3A RMS continuous, 80A RMS for 1 second (with 12AWG section wire)
HACS REMOTE SENSORS	
Depends on sensor rating. See HACS datasheet	
SAMPLING RATE MEASUREMENT	
Sampling rate	128 samples/cycle

**OPTIONAL RELAY OUTPUTS**
**ELECTROMECHANICAL RELAY**

Dry Contact, Option (4DI/DO or 12DI/DO Optional module)

 2 or 4 relays rated at 5A/250 VAC;  
 5A/30 VDC, 1 contact (SPST Form A)

 Galvanic isolation → Between contacts and coil: 3000 VAC 1 min  
 → Between open contacts: 750 VAC

Operate time 10 ms max

Release time 5 ms max

Update time 1 cycle

 Wire size 14 AWG (up to 1.5 mm<sup>2</sup>)

**SOLID STATE RELAY OPTION**

(4DI/2DO Optional Module)

2 relays rated at 0.15A/250 V AC/DC, 1 contact (SPST Form A)

Galvanic isolation 3750 VAC 1 min

Operate time 1 ms max

Release time 0.25 ms max

Update time 1 cycle

Connector type Removable, 4 pins

 Wire size 14 AWG (up to 1.5 mm<sup>2</sup>)

**OPTIONAL DIGITAL INPUTS**

4 or 12 Digital Inputs (4DI/2DO or 12DI/4DO Optional module) Dry Contacts, internally wetted @ 24VDC or Wet contact @ 250VDC (12DI/4DO only)

 Sensitivity Open @ input resistance >100 k $\Omega$ , Closed @ Input resistance < 100  $\Omega$ 

Galvanic isolation 3750 VAC 1 min

Internal power supply 24VDC, 4DI/2DO or 12DI/4DO

External power supply 250V DC (12DI/4DO only)

Scan time 1 ms

Connector type Removable, 5 pins

 Wire size 14 AWG (up to 1.5 mm<sup>2</sup>)

**OPTIONAL ANALOG OUTPUTS**

4 Analog Outputs optically isolated (AO Optional module)

 Ranges →  $\pm 1$  mA, maximum load 5 k $\Omega$  (100% overload)  
 → 0-20 mA, maximum load 510  $\Omega$   
 → 4-20 mA, maximum load 510  $\Omega$   
 → 0-1 mA, maximum load 5 k $\Omega$  (100% overload)

Isolation 2500 VAC 1 min

Power supply Internal

Accuracy 0.5% FS

Update time 1 cycle

Connector type Removable, 5 pins

 Wire size 14 AWG (up to 1.5 mm<sup>2</sup>)

**COMMUNICATION PORTS**
**COM1**

RS-485 optically isolated port

Isolation 3000 VAC 1 min

Baud rate up to 115.2 kbps

Supported protocols Modbus RTU, DNP3, and SATEC ASCII

Connector type Removable, 3 pins

 Wire size Up to 14 AWG (up to 1.5 mm<sup>2</sup>)

**COM2 (Optional module)**
**ETHERNET PORT**

Transformer-isolated 10/100BaseT Ethernet port.

Supported protocols Modbus/TCP (Port 502), DNP3/TCP (Port 20000)

Number of simultaneous connections 4 (2 Modbus/TCP + 2 DNP3/TCP)

Connector type RJ45 modular

**GPRS PORT**

Supported protocols Modbus/TCP (Port 502)

Connector type SMA

**Profibus DP (IEC 61158)**

RS-485 optically isoated Profibus interface

Connector type Removable, 5 pins

 Baud rate 9600 bit/s – 12 Mbit/s  
(auto detection)

32 bytes input, 32 bytes output

Supported protocols PROFIBUS DP

**RS-232/422-485 PORT**

RS-232 or RS-422/485 optically isolated port

Isolation 3000 VAC 1 min

Baud rate Up to 115.2 kbps

 Supported protocols Modbus RTU, DNP3, and SATEC  
ASCII

 Connector type Removable, 5 pins for  
RS-422/485 and DB9 for RS-232

 Wire size Up to 14 AWG (up to 1.5 mm<sup>2</sup>)

**REAL-TIME CLOCK**

 Standard Meter Clock → Non-backed clock  
→ Accuracy: typical error 1  
minute per month @ 25°C  
→ Typical clock retention time:  
30 seconds

 TOU Module Meter Clock → Battery-backed clock  
→ Accuracy: typical error 7  
seconds per month @ 25°C  
(±2.5ppm)  
→ Typical clock retention time:  
36 months

**DISPLAY MODULE**

 3.5" LCD Monochrome Display, 240 x 128 dots  
resolution

Tri-color LED load bar graph 4(0-)%110

COM1 RXT/X activity LED

Diagnostics indication LED

kWhk/varh Pulse LED f(or E and EH models)

Keyp :ad5 push buttons

## Standards Compliance

### Accuracy

- Complies IEC62053-22, class 0.5S
- Meets ANSI C12.20 –1998, class 10 0.5%

### Electromagnetic Immunity

- Comply with IEC 61000-6-2:
  - IEC 61000-4-2 level 3:  
Electrostatic Discharge
  - IEC 61000-4-3 level 3:  
Radiated Electromagnetic RF Fields
  - IEC 61000-4-4 level 3:  
Electric Fast Transient
  - IEC 61000-4-5 level 3: Surge
  - IEC 61000-4-6 level 3:  
Conducted Radio Frequency
  - IEC 61000-4-8:  
Power Frequency Magnetic Field
  - Meets ANSI/IEEE C37.90.1:  
Fast Transient SWC

### Electromagnetic Emission

- Comply with IEC 61000-6-4:  
Radiated/Conducted class A
- Comply with IEC CISPR 22:  
Radiated/Conducted class A

### Safety/Construction


- Meets IEC 61010-1: 2006

### AC and Impulse Insulation

- Comply with IEC 62052-11: 2500 VAC during  
1 minute
- 6KV/500Ω @ 1.2/50 μs impulse

## PM135 Order String

MODEL		
Power Version	PM135P	<input type="text"/>
Energy and Harmonic Version	PM135EH	
Energy Only	PM135E	
OPTIONS		
Current Inputs		
5 Ampere	5	<input type="text"/>
1 Ampere	1	
5A split core remote high accuracy current sensor (HACS)	RS5	
High Accuracy Current Sensors (HACS). Requires ordering of 3 HACS (refer to HACS datasheet)	HACS	
Calibration at Frequency		
25 Hz	25HZ	<input type="text"/>
50 Hz	50HZ	
60 Hz	60HZ	
400 Hz	400HZ	
Resolution		
Low Resolution 1A, 1V	-	<input type="text"/>
High Resolution 0.01A, 0.1V	H	
Power Supply		
85-265V AC and 85-290V DC	ACDC	<input type="text"/>
9.5-18V DC	1DC	
18.5-58V DC (24VDC, 48VDC)	23DC	
Communication Protocol		
Modbus and DNP 3.0	-	<input type="text"/>
Modbus and IEC 60870-101/104	870	
Display Language		
English	EN	<input type="text"/>
Russian	RU	
Spanish	ES	
Mounting		
Panel Mount (standard)	-	<input type="text"/>
DIN Rail Mounting	DIN	
Expansion Module (Max. 1 module per instrument, can be ordered separately)		
4 Analog Outputs: ±1mA	AO1	<input type="text"/>
4 Analog Output: 0-20mA	AO2	
4 Analog Output: 0-1mA	AO3	
4 Analog Output: 4-20mA	AO4	
4 Analog Output: 0-3mA	AO5	
4 Analog Output: ±3mA	AO6	
4 Analog Output: 0-5mA	AO7	
4 Analog Output: ±5mA	AO8	
Communication: Ethernet (TCP/IP)	ETH	<input type="text"/>
Communication: PROFIBUS	PRO	
Communication: RS232/422/485	RS232	
Communication: 2G/3G GSM Modem *	T3G	
Communication: 2G/3G CDMA Modem *	T3C	
Communication: RF (see note)**	RF-x-y	
4 Digital Inputs (Dry Contact) / 2 Relay Outputs 250V / 5A AC	DIOR	
4 Digital Inputs (Dry Contact) / 2 SSR Outputs 250V / 0.1A AC	DIOS	
4 Digital Inputs (Dry Contact) / TOU / RTC Battery	TOD	
12 Digital Inputs (Dry Contact) / 4 Relay Outputs 250V/5A AC	12DIOR-DRC	
12 Digital Inputs (125VDC) / 4 Relay Outputs 250V/5A AC	12DIOR-125V	
12 Digital Inputs (250VDC) / 4 Relay Outputs 250V/5A AC	12DIOR-250V	
12DIOR-DRC with Ethernet	12DIOR-DRC-ETH	
12DIOR-125V with Ethernet	12DIOR-125V-ETH	
12DIOR-250V with Ethernet	12DIOR-250V-ETH	
12DIOR-DRC with RS-485	12DIOR-DRC-485	
12DIOR-125V with RS-485	12DIOR-125V-485	
12DIOR-250V with RS-485	12DIOR-250V-485	



Innovative Electronics For You

## M. B. Control & Systems Pvt. Ltd.

### Corporate Office

31/1, Ahiripukur Road, Kolkata 700019, West Bengal, India

Call : +91 98313 30473, 98312 06454 | Fax : +91 033 2287 0445

Email : enquiry@mbcontrol.com

service@mbcontrol.com (for service related queries only)

Website : www.mbcontrol.com

### Notes

\* RF module and accessories are available in certain regions only. Please consult your local supplier.

\*\* Does not support 870 protocol.